



compressors

LET'S SOLVE AIR

AIR DRYER SELECTION / SPECIFICATIONS

- ➡ WATER COOLED (REFRIGERATED) AIR DRYER 1/2" or 3/4" BSP WATER CONNECTIONS
- ➡ WITH 0.1 MICRON STAINLESS STEEL DUST FILTER 2" 300 LBS FLANGED CONNECTIONS
- ➡ INLET AIR PRESSURE MAXIMUM : 42 BAR
- ➡ INLET AIR TEMPRATURE MAXIMUM : 50⁰C
- ➡ INLET CONNECTION FLANGE TYPE 2" 300 LBS
- ➡ DEW POINT TEMPRATURE : 3⁰C

MACHINE	MODEL	CAPACITY FAD M ³ /H	CAPACITY FAD CFM	SPEED - RPM	Motor power KW
AJ 11	AJ 11-N	187	110	450	37
	AJ 11-A	238	140	560	45
	AJ 11-V	289	170	680	55
AJ 20	AJ 20-N	407	240	450	75
	AJ 20-A	492	290	550	90
	AJ 20-V	594	350	665	110
AJ 29	AJ 29-N	815	480	365	160
	AJ 29-A	1001	590	445	200
	AJ 29-V	1188	700	530	250